

Workshop Starter Package



FEATURES

Wheel Balancer

- Single phase 240V Electronic wheel balancer
- Hand spin balancing technology
- Light weight in construction but durable to cope with the heaviest of wheels
- Manual clamping nut with hand spin facility
- Technologies achieving a zero balance every spin
- Accurate to 1g
- Full Alloy programme facility 4 programmes in total
- 12 V option available as an option (Ideal for mobile tyre fitting)
- Bolts securely & safely to any concrete floor
- Manual input of data
- Self calibrating machine (Operator can calibrate periodically making sure of accurate tolerances)
- Set of 4 mounting cones as standard incorporating small four wheel drive cone as standard
- Heavy duty wheel rim width callipers
- Balance weight pliers as standard
- Compact unit for confined spaces
- Manual foot brake for easy weight location
- Cone mounting lugs on machine body for easy storage
- Full CE approval
- Motorcycle adaptor (Optional Extra)
- 3,4,5 universal flange plate adaptor (Centre less wheel adaptor) (Optional Extra)
- Small weight tray durable in construction
- 24 months warranty*

*Terms & conditions apply

TECHNICAL DATA

- Max. Wheel Weight - 65 kg
- Balancing Accuracy - +/- 1g
- Rim Diameter - 10" - 24"
- Rim Width - 1.5" - 20"
- Balancing / Shaft Speed - 80 rpm
- Measuring Time - 8 secs
- Weight - 90 / 65 kg
- Display Screen - Digital LED

Workshop Starter Package



FEATURES

Tyre Changer

- Swing Arm Tyre Changer
 - Compact unit can be mounted close to wall
 - Heavy & durable in construction
 - Standard - Semi professional machine
 - Steel fitting head
 - Plastic protection kit supplied as standard (jaw clamping, fitting head insert and bead breaker blade)
 - 2500 kg of bead breaker blade
 - Heavy duty bead breaker blade
 - Strong bead breaker arm
 - Fully integrated filter regulator lubricator for quality air supply
 - Foot pedal operation
 - Full length abutment pad for breaking the bead of the tyre
 - Integrated tyre inflator
 - Full jaw inflation (enables the tyre to be inflated & bead sealed whilst being clamped on the turntable of the tyre changer) as standard
 - Integrated tyre inflator
 - Heavy duty jaw clamp cylinders
 - 240V Electrical supply as standard (3phs optional extra available)
 - Maximum wheel diameter clamping 12" - 24" inside clamping | 10" - 21" outside clamping
 - 24 months warranty
- *Terms & conditions apply

TECHNICAL DATA

- Power Supply - 240V (3 Phase available)
- Max. Wheel Diameter - 41"
- Max. Wheel Width - 14"
- Outside clamping - 10" - 21"
- Inside clamping - 12" - 24"
- Air Supply - 8 Bar
- Bead Braker Force - 2500 kg
- Package Size - 960 x 760 x 930mm
- Weight - 187 kg

Workshop Starter Package



FEATURES

Post Lift

- Dual hydraulic cylinders, direct drive
- Dual point automatic lock release (electromagnetic)
- Two-Stage telescopic lifting arms
- Spiral step-less adjustment arm tray, option extension adapter
- Mechanical safety device, both side manual unlocking, manual drop-down
- Italian made parachute valve under each cylinder in case of hydraulic hose failure
- Relief valve to prevent overloading
- Door opening protection rubber
- Lift height limit safety system
- Synchronization cable
- Aluminum shell motor, 24V low voltage control system
- Emergency manual drop function with adjustable dropping speed
- Machine Welded for extra stability
- 24 months warranty*

*Terms & conditions apply

TECHNICAL DATA

- Capacity – 4000 kg
- Rise Time – 45 secs
- Drop Time - 45 secs
- Lifting Height - 1930mm
- Min. Height - 100mm
- Overall Height - 3724mm
- Overall Width – 3366mm
- Distance Between Columns - 2506mm
- Short Arm Length - 680 - 1020mm
- Long Arm Length - 860 - 1300mm
- Motor Power - 220V / 50Hz / 1 Ph / 3KW

Workshop Starter Package



FEATURES

Compressor

- Automotive duty rated
 - Air receivers 2014/29/EU standard
 - High efficiency air pumps
 - Auto stop / start
 - Low vibration levels
 - Deep finned cast iron pump
 - Thermal protection to all motors
 - Spares & service nationwide
 - Exports worldwide
 - 24 months warranty*
- *Terms & conditions apply

TECHNICAL DATA

- | | | |
|-----------------------|-----------------------|-------------------|
| • Stock Code – CM1112 | • LTS FAD – 144 | • MAS PSI - 150 |
| • Model – EV9/ 100-1 | • Stage - 1 | • Length – 1010mm |
| • CFM DISP – 9.0 | • HP - KW – 2.0 - 1.5 | • Width - 370mm |
| • LTS DISP – 255 | • CYL NO – 2 | • Height - 750mm |
| • CFM FAD – 5.1 | • REC LT – 100 | • Weight - 75kg |