

Workshop Starter Package Pro Plus



FEATURES

Wheel Balancer

- Single phase 240V Electronic wheel balancer
- Strong and durable cabinet
- Stylish weight tray
- Technologies achieving a zero balance every spin
- Quick release clamping nut
- Accurate to 1g
- Full Alloy programme facility 4 programmes in total
- Bolts securely and safely to any concrete floor
- Bolts securely and safely to any concrete floor
- Automatic data input for wheel diameter and wheel offset on the shaft

- Self calibrating machine (Operator can calibrate periodically making sure of accurate tolerances)
- Set of 4 mounting cones as standard incorporating small four wheel drive cone as standard
- Rear cone mounting spring
- Heavy duty wheel rim width callipers
- Balance weight pliers as standard
- Wheel guard to protect
- Digital Display screen
- Full CE approval
- Motorcycle adaptor (Optional Extra)
- 3,4,5 universal flange plate adaptor (Centre less wheel adaptor) (Optional Extra)
- 24 months warranty*

TECHNICAL DATA

- | | | |
|-------------------------------|-------------------------------------|--------------------------------|
| • Max. Wheel Weight - 65 kg | • Balancing / Shaft Speed - 200 rpm | • Measuring Time - 8 secs |
| • Balancing Accuracy - +/- 1g | • Rim Diameter - 10" - 24" | • Weight - 122 / 98 kg |
| • Rim Diameter - 10" - 24" | • Rim Width - 1.5" - 20" | • Display Screen - Digital LCD |

Workshop Starter Package Pro Plus



FEATURES

Tyre Changer

- Fully integrated power assisted arm for run flat and low profile tyres
- Full jaw inflation (Enables the tyre to be inflated & bead sealed whilst being clamped on the turntable of the tyre changer) as standard
- Standard – semi professional machine
- Semi automatic with tilting arm (air operated)
- Heavy and durable in construction
- Steel fitting head
- Plastic protection kit supplied as standard (jaw clamping, fitting head insert and bead breaker blade)
- 2500 kg of bead breaker blade
- Heavy duty bead breaker blade
- Strong bead breaker arm
- Fully integrated filter regulator lubricator for quality air supplyable of the tyre changer) as standard
- Foot pedal operation
- Full length abutment pad for breaking the bead of the tyre
- Integrated tyre inflator
- Heavy duty jaw clamp cylinders
- 240V Electrical supply as standard (3phs optional extra available)
- 24 months warranty

*Terms & conditions apply

TECHNICAL DATA

- Power Supply - 240V (3 Phase available)
- Max. Wheel Diameter - 41"
- Max. Wheel Width - 14"
- Outside clamping - 10" - 21"
- Inside clamping - 12" - 24"
- Air Supply - 8 Bar

Workshop Starter Package Pro Plus



FEATURES

Post Lift

- 5 Tonne twin hydraulic 2 post lift
- Low profile base plate not load bearing
- Triple telescopic arms for full access to jacking points
- Button operation for decent fully electric lowering system 24V circuit
- Synchronising cables as standard
- Top limit and safety switches fitted
- Full CE approval
- Heavy duty hydraulic pump unit
- Quality control box
- Low voltage operating system

- Height extensions as standard
- Hydraulic safety system in case of hydraulic hose burst
- Safety cut out breakers internal to control box
- Heavy duty arm configuration
- Post covers for health and safety
- Heavy duty arm locking mechanisms
- Adjustable lifting pads
- 24 months warranty*

*Terms & conditions apply

TECHNICAL DATA

- Lifting Capacity – 5000 kg
- Weight – 920 kg
- Max Lifting Height - 1900mm
- Electricity Supply – 240V / 415V option
- Rated Oil Pressure - 22 MPA
- Lifting Time - 55 secs

Workshop Starter Package Pro Plus



FEATURES

Compressor

- Automotive duty rated
- Air receivers 2014/29/EU standard
- High efficiency air pumps
- Auto stop / start
- Low vibration levels
- Deep finned cast iron pump
- Thermal protection to all motors
- Spares & service nationwide
- Exports worldwide
- 24 months warranty*

*Terms & conditions apply

TECHNICAL DATA

- | | | |
|-----------------------|-----------------------|-------------------|
| • Stock Code – CM1112 | • LTS FAD – 144 | • MAS PSI - 150 |
| • Model – EV9/ 100-1 | • Stage - 1 | • Length – 1010mm |
| • CFM DISP – 9.0 | • HP - KW – 2.0 - 1.5 | • Width - 370mm |
| • LTS DISP – 255 | • CYL NO – 2 | • Height - 750mm |
| • CFM FAD – 5.1 | • REC LT – 100 | • Weight - 75kg |